CHESTERTON
Global Solutions, Local Service.





273

ELECTRIC MOTOR CLEANER

PRODUCT DATA SHEET

APPLICATION AREAS

- *Electrical Equipment*
- *Electric Motors*
- *Machine Shops*
- *Blowers/Fans*
- *Automotive*
- *Manufacturing*

KEY FEATURES AND BENEFITS

- Non-flammable
- Non-conductive
- High dielectric strength
- Fast penetration - high solvency
- NSF K2 registration number 133975 (bulk) and 133976 (aerosol)

PACKAGING

Aerosol

20L

DIRECTIONS

Parts to be cleaned can be immersed in Chesterton 273 Electric Motor Cleaner or cleaned with spray or brush. Residue should be removed with dry air, taking care to avoid splatter. Dry before returning to service. On plastic, paint or rubber, test small area before using. Be certain to relubricate as neccessary.

DESCRIPTION

Chesterton® 273 Electric Motor Cleaner is a non-flammable, non-conductive and non-corrosive solvent based degreaser. It can be used on operating equipment and electrical systems without concern as to fire hazard. The product instantly cuts through power-robbing grease, dirt, grime, tar, oil and other materials usually found around electrical equipment, machine shops, manufacturing plants, marine electrical instrumentation and automotive applications. Chesterton 273 Electric Motor Cleaner removes these conductive soils that could otherwise cause dangerous electrical short circuits. Applied at regular intervals together with routine inspection and periodic maintenance, 273 Electric Motor Cleaner will assure continued, high output and prolong the life of electrical equipment.



Before using this product, please refer to Safety Data Sheet (SDS).

TYPICAL PHYSICAL PROPERTIES

Appearance	Clear, Colorless
Flash Point	None
Specific Gravity	1,6
Density	1,6 kg/l (13 lbs/gal)
Residue	None
Dielectric Strength (ASTM D-877)	24,2 Kv

CHESTERTON
Global Solutions, Local Service.

860 Salem Street, Groveland, MA 01834 USA
978-469-6888 chesterton.com
© 2026 A.W. Chesterton Company
® Registered trademark owned by A.W. Chesterton Company in USA and other countries, unless otherwise noted.

Technical Data reflects results of laboratory tests and is intended to indicate general characteristics only. Since many actual application circumstances are beyond Chesterton's knowledge and/or control, the product user must determine the suitability of the products it intends to use for its particular purpose and assume all risks and liabilities in connection therewith. CHESTERTON DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.