Version	**:**	**1**
Date	**:**	**january 08, 2017**

ANTIFREEZE BS

Description

Antifreeze BS is a classic antifreeze for use in cooling systems of internal combustion engines, heat exchange systems, solar collectors and central heating installations. Antifreeze BS does not contain nitrite, amine and phosphate. In order to protect the (cooling) system against corrosion a minimum of 30% Antifreeze BS and 70% demineralized water is recommended for the full year.

Specifications

ASTM D3306 | ASTM D 4985 | SAE J 1034 | BS 6580 (1992) | AFNOR NF R15-601

Typische standaardanalyses

Density 15° C	kg/m3	1119
Colour		blauw
pH–value (50% vol. Antivries BS)		7,8
Reservealkality	ml HCL 0,1N	20,5
Freezing Point 50% vol. Antifreeze BS	°C	-37
Boiling Point	°C	170
Water content	%	4

Volume	Art.no.
1 ltr	390561
4 ltr	390564
5 ltr	390565
20 ltr	3905620
60 ltr	3905660
208 ltr	39056208
bulk	39056

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.