Version	:	**1**
Date	:	**August 4, 2018**

ANTIFREEZE G11

Description
Antifreeze G11 is a silicate-containing, top qualitty antifreeze which complies with VW TL 774C .

Application
This antifreeze can be used throughout the whole year in the cooling systems of petrol and diesel engines. Thanks to the special additives package and the high quality mono-ethylene glycol this Antifreeze G11 is one of the highest quality on the market. This antifreeze should be further diluted before use with water in the recommended ratio.

Specifications
BS 6580 | FVV Heft R 443 | Afnor R 15/601 | SAE J 1034 | JIS K 2234 | KSM 2142
CUNA NC 956-16 | UNE 26361-88 | EMPA | ASTM D 3306/4985 | NATO S 759
E/L 1415c (MIL Italy)

OEM specifications
Porsche/VW/Audi/Seat/Skoda TL 774 C | Mercedes DBL 7700 (325.0) | Ford ESD M97 B49-A
Man 324NF | GM US 6277 M | Ford WSS-M97B44-C | Chrysler MS 9176 | BMW N 600 69.0
VOLVO (Reg. No 260) | FORD ESD M97 B49-A | OPEL GM QL 130100

Typical Characteristics

Density 15° C	kg/m3	1125
Color		Green/Blue
pH–value		9,4
Boiling point	°C	175
Reserve alkalinity		15,4
Hard water resistance		Clear

Volume	Art.no.
1 ltr	390381
4 ltr	390384
5 ltr	390385
20 ltr	3903820
60 ltr	3903860
208 ltr	39038208
bulk	39038

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.