Version : **1.1**
Date : **Novembre 22 2024**

ANTIFREEZE G12+ RED

Description
Antifreeze G12+ Red is a modern antifreeze on mono ethylene glycol-base which makes use of 'Organic Acid Technology' (OAT) and is free of nitrite, amines, phosphates and silicates.

Application
Antifreeze G12+ can be used in water-cooled internal combustion engines, heat exchange systems, solar collectors and central heating installations. In order to protect the cooling system against corrosion, a ratio of at least 30% Antifreeze G12 + and 70% demineralized water is a recommended for the full year.

Specifications
AFNOR NF R15-601 | ASTM D 3306 | ASTM D 4985 | SAE J 1034 | BS 6580 | FFV Heft R443 | CUNA NC 956-16 | UNE 26361-88 | JIS K2234 | NATO S 759 | DAF 74002 | Chrysler MS 9176 | Cummins 85T8-2 & 90T8-4 | Ford ESE M97B49-A/ WSS-M97B44-D/ESD M97 B49-A | GM 1899 M | US 6277M/OPEL GM QL130100 | John Deere H 24 B1 & C1 | Leyland Trucks | LTS22AF10 | Mack 014GS 17004 | Volvo MAN 248/324 (SNF)/B&W D36 5600 | MB pag. 325.3 | Renault 41-01-001 | VAG TL 774F | Volvo

Typical Characteristics

Density at 15 °C, kg/l	:	1,118
Color	:	Red
pH-value	:	8,2
Boiling point °C	:	175

Volume	Art.no.
1 ltr	390801
4 ltr	390804
5 ltr	390805
20 ltr	3908020
60 ltr	3908060
208 ltr	39080208
bulk	39080

UTB B.V.
Kamerling Onnesweg 28-30
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.