Version : **1.1**
Date : **18 august 2026**

COPPER PASTE

Characteristics

Copper Paste is a copper containing assembling paste with extra-ordinary lubricating properties. The product prevents fretting during assembling and provides for a loose screw-connection, also after a long-term influence of heat and atmospheric effect. Moreover the product contains water repellent components and protects against corrosion.



Application

Copper Paste is very suitable as a mounting paste for all parts and threads that are normally treated with metal-containing paste. For example, Copper Paste can be used for the lubrication and protection of, for example, threaded connections, rolling and sliding bearings, chains, fitting edges, splines, brake parts and compressed air tools. Apply Copper Paste thinly on a, preferably clean and dry, surface. Do not mix with other greases. Copper Paste can also be used by means of grease guns and central lubricators.

Properties

- Universal anti-seize / assembly paste
- Protects against corrosion and wear
- Enriched with copper particles
- Excellent lubrication
- Water-repellent
- Great thermal stability

Volume	Art.no.
200 ml	72045200

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.