Version : **1.1**
Date : **Novembre 22 2024**

EXCELGEAR ATF IIIG

Description
Excelgear ATF IIIG is a semi- synthetic, very high quality ATF, complying with the latest Ford Mercon, GM Dexron III and many other specifications. It ensures excellent low temperature pumpability and has exceptionally high temperature properties against thermal oxidation and degradation.

Application
This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIIH fluid is required.

Specifications
Allison C4/TES-389 | Cat TO-2 | MAN 339 Typ Z1/V1 | Ford Mercon/M2C138-C/166-H | Volvo 97341 | GM Dexron IID/IIE/IIIF/IIIG/IIIH | MB 236.1/236.5/236.6/236.7/236.9 | Voith 55.6335 (G607) | ZF-TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C

Typical Characteristics

Density at 15 °C, kg/l	:	0,848
Viscosity 40 °C, mm^2/s	:	36,00
Viscosity 100 °C, mm^2/s	:	7,30
Viscosity Index	:	175
Flash Point COC, °C	:	226
Pour Point, °C	:	-48

Volume	Art.no.
1 ltr	320761
4 ltr	320764
5 ltr	320765
20 ltr	3207620
60 ltr	3207660
208 ltr	32076208
bulk	32076

UTB B.V.
Kamerling Onnesweg 28-30
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.