Version : 1.2
Date : may 4 2020

EXCELGEAR HD 85W140

Description

Excelgear HD 85W140 is a lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP-additives to obtain the following properties:
- an excellent resistance against oxidation
- a very high activity against wear, corrosion and foam
- a low pour point
- very good EP-properties
- good clutch-switch performance

Application

Excelgear HD 85W140 is a gear oil for transmissions and mechanical transmissions composed of high quality mineral base oils and Extreme Pressure (EP) additives. Can be used in heavy duty mechanical drives such as transmissions, (hypoid) differentials, final drives and cardans.

Specifications

API GL5 | MB 235.0 | MAN 342 M-1/M2 |MIL-L-2105D/C |VOLVO97310/97316
| ZF-TE-ML 05A/07A/12E/16B/16C/16D/17B/19B

Typical Characteristics

Viscosity class	-	SAE 85W140
Density at 15 °C,	kg/l	0,904
Kin. Viscosity 40 °C,	mm^2/s	340.00
Kin. Viscosity 100 °C,	mm^2/s	27,00
Viscosity Index		96
Flash Point COC,	°C	245
Pour Point,	°C	-15

Volume	Art.no.
1 ltr	320781
4 ltr	320784
5 ltr	320785
20 ltr	3207820
60 ltr	3207860
208 ltr	32078208
bulk	32078

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply.
Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.