Versie: 1.2
Datum : may, 4 2020

EXCELGEAR LS 80W90

Description

Excelgear LS 80W90 is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP-additives to obtain the following properties:
- an excellent resistance against oxidation
- a very high activity against wear, corrosion and foam
- a low pour point
- very good EP-properties
- excellent "Limited Slip" properties

Application

Excelgear LS 80W90 has especially been developed for the perfect lubrication of so-called “Limited Slip” and “Auto-Locking” hypoid transmissions. Excelgear LS 80W90 /85W140 can be used in heavy duty mechanical drives such as transmissions, (hypoid) differentials, final drives and cardans with or whithout Limited Slip and Auto Locking.

Specifications

API GL5-LS | MIL-L-2105C/D

Typical Characteristics

Density at 15 °C,	kg/l	0,897
Kin. Viscosity 40 °C,	mm²/s	150
Kin. Viscosity 100 °C,	mm²/s	15.10
Viscosity Index		100
Flash Point COC,	°C	210
Pour Point,	°C	-30

Volume	Art No
1 ltr	320891
4 ltr	320894
5 ltr	320895
20 ltr	3208920
60 ltr	3208960
208 ltr	32089208
bulk	32089

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.