Version : **2**
Date : **23 January 2026**

EXCELLO CHAINSAW BIO 100

Characteristics
This is a chain-saw oil based upon total biodegradable vegetable oils under addition of special additives to obtain the tackiness and lubricity of the oil. The base oil of this biodegradable chain-saw oil and the special selected additives will be degraded by the environment in short time. Even at high temperatures this oil keeps a high grade of tackiness, preventing the oil to fling of the chain.

Application
This product has been especially formulated to lubricate the chain, preventing the chain from overheating and loss of strength. The chain-saw oil cannot be used for the lubrication of the engine of the saw.

Specifications
Biodegradability according OECD 301 B >75%

Typical properties

Density at 15°C	kg/L	0,919
Viscosity 40°C	cSt	102
Viscosity 100°C	cSt	23.80
Viscosity Index		264
Flash Point COC	°C	318
Pour Point	°C	-21

Volume	Art.no.
1 ltr	310991
4 ltr	310994
5 ltr	310995
20 ltr	3109920
60 ltr	3109960
208 ltr	31099208
bulk	31099

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.