Version : **1.1**
Date : **22 Novembre 2024**

EXCELLO CHAINSAW OIL 100

Description
Excello Chainsaw Oil 100 is based upon high quality low aromatic solvent-refined base oils under addition of special additives to obtain the following properties:

- a very high grade of tackiness, preventing the oil from fling of the chain

- excellent lubricity

Applications
This chain-saw oil has been specially formulated to lubricate the chain of chain-saws preventing this oil from overheating and loss of strength. The high grade of tackiness prevents the oil to fling from the chain. The chain-saw oil cannot be used for the lubrication of the engine of the saw.

Specifications
ISO 6743-1 AC

Typical Characteristics

Density at 15 °C,	kg/l	0,881
Viscosity 40 °C,	mm^2/s	100,00
Viscosity 100 °C,	mm^2/s	11,30
Viscosity Index		98
Flash Point ,	°C	230
Pour Point,	°C	-24

Volume	Art.no.
1 ltr	310181
4 ltr	310184
5 ltr	310185
20 ltr	3101820
60 ltr	3101860
208 ltr	31018208
bulk	31018

UTB B.V.
Kamerlingh Onnesweg 28-30
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.