Version : 1.2
Date : may 01 2020

EXCELLO COMPRES VRD 46/68

Description

Excello Compres VRD is based upon top-grade selected solvent-refined base oils, with a natural high resistance against oxidation. Under addition of additives this compressor oil meets the following properties:
- low carbon-forming tendencies
- good oxidation stability
- a very good protection against corrosion
- good anti-wear properties
- low volatility

Application

Excello Compres VRD is recommended for the crankcase and cylinder lubrication of reciprocating air compressors, but also for the lubrication of drip feed rotary sliding vane compressors. This compressor oil has low carbon-forming tendencies and minimises the formation of deposits in the discharge system at the temperature range where these compressors operate.

Specifications

DIN 51506 VDL | DIN 51352, 2

Typical Characteristics			46	68
Density at 15 °C,	kg/l	:	0,871	0.876
Viscosity 40 °C,	mm^2/s	:	46.00	68.00
Viscosity 100 °C,	mm^2/s	:	5.36	8.77
Viscosity Index		:	102	101
Flash Point PM,	°C	:	224	236
Pour Point,	°C	:	-39	-33
Acid number,	mgKOH/g	:	0.45	0.45

Volume	Art.no. ISO VG 46	ISO VG 68
1 ltr	350321	350331
4 ltr	350324	350334
5 ltr	350325	350335
20 ltr	3503220	3503320
60 ltr	3503260	3503360
208 ltr	35032208	35033208
bulk	35032	35033

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply.
Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.