Version : **1.1**
Date : **22 Novembre 2024**

EXCELLO OUTBOARD 2T

Description
Excello Outboard 2T is oil for water-cooled 2-stroke outboard engines, meeting the NMMA-specification TC-W3. It's ashless composition prevents the formation of deposit, pre-ignition and spark plug fouling. High protection against rust and corrosion.

Applications
This ashless two stroke engine oil is excellent suitable for use in powerfull water-cooled two stroke outboard engines. This oil is also suitable for Direct Fuel Injection. It is recommended to adhere to the mixing ratio prescribed by the manufacturer when mixing.

Specifications
NMMA TC-W3
OMC 40/70

Typical Characteristics

Density at 15 °C,	kg/l	0,876
Viscosity 40 °C,	mm^2/s	35,60
Viscosity 100 °C,	mm^2/s	6,29
Viscosity Index		126
Flash Point ,	°C	107
Pour Point,	°C	-30

Volume	Art.no.
1 ltr	310681
4 ltr	310684
5 ltr	310685
20 ltr	3106820
60 ltr	3106860
208 ltr	31068208
bulk	31068

UTB B.V.
Kamerlingh Onnesweg 28-30
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.