Version : **2**
Date : **23 January 2026**

EXCELLO REGULAR DD 40

Characteristics

Excello Regular DD 40 is a motor oil based on high-quality refined base oils, to which balanced additives have been added to achieve the following properties:

- low sulfated ash content;
- strong anti-wear, anti-corrosion, and anti-foam properties;
- very strong detergency, which minimizes deposits in the hot zone;
- very strong dispersancy, which significantly reduces deposits and sludge formation.

Application

Excello Regular DD 40 is a special engine oil for two-stroke diesel engines. This product is suitable for applications requiring an API CF-2 or CD-II grade of the high viscosity which give a strong oil film.

Specifications

API CF/CF-2/SF | Allison C-4

Typical properties

Viscosity grade		SAE 40
Density at 15°C	kg/L	0,895
Viscosity 40°C	cSt	141.9
Viscosity 100°C	cSt	14.10
Viscosity Index		98
Flash Point COC	°C	240
Pour Point	°C	-20
Total Base Number	mgKOH/g	7.3
Sulphate Ash	%mass	0.95

Volume	Art.no.
1 ltr	310231
4 ltr	310234
5 ltr	310235
20 ltr	3102320
60 ltr	3102360
208 ltr	31023208
bulk	31023

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.