Version : **2**
Date : **23 January 2026**

EXCELLO REGULAR SAE 10

Characteristics

Excello Regular is a universal engine oil for diesel engines with or without turbo under the most severe conditions. The product is also suitable for gearboxes, torque converters and hydraulic systems if the manufacturer prescribes.

- Performance in keeping the engine clean.

Application

This engine oil is highly recommended for fixed diesel engines, material for public works and mixed fleets of trucks and cars.

Specifications

API CF-4/SF/SG | ACEA C2-96 issue 5 | MB 227.0/228.0 | MAN 270 | CAT TO-2 | MTU Category 1

Typical properties

Density at 15°C	kg/L	0,845
Viscosity 40°C	cSt	33.4
Viscosity 100°C	cSt	6.8
Viscosity Index		125
Flash Point COC	°C	206
Pour Point	°C	-36
Total Base Number	mgKOH/g	7.8
Sulphate Ash	%mass	0.88

Volume	Art.no.
1 ltr	310201
4 ltr	310204
5 ltr	310205
20 ltr	3102020
60 ltr	3102060
208 ltr	31020208
bulk	31020

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.