Version : 1.3
Date : August 5th, 2024

EXCELLO SHPD 15W40

Description

Excello SHPD 15W40 is a "new generation" gasoline- and diesel engine oil, formulated with solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:
- a low sulphated ash number;
- a high and stable viscosity index;
- a powerful activity against corrosion and foam;
- a very powerful detergency prevents deposits in the engine;
- a very strong dispersion that prevents from precipitation and sludge;
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners.

Application

Excello SHPD 15W40 is applicable to gasoline and light to heavy diesel engines with or without turbo under the toughest operation conditions. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This special quality of engine oil is mainly developed to allow extended oil drain intervals in EURO 2, 3 and 4 diesel engines.

Meets performance of

ACEA A3/B3/B4/E5/E7 | API CF/CI-4/SL | CUMMINS CES 20077/20078 | CAT ECF 1a/ECF-2/ TO-2 | Alliaon C3 | Detroit Diesel 93K215 | GLOBAL DHD-1 | MTU-category 2 | Deutz DQC III-10/18 | MAN M 3275-1 | MB 228.3 | MACK EO-M+/EO-N | Renault VI RLD-2 | Volvo VDS 3

Typical Characteristics

Viscosity class	-	SAE 15W40
Density 15° C	kg/l	0,870
Kin. Viscosity 40°C	mm2/s	103
Kin. Viscosity 100°C	mm2/s	14,4
Viscosity index	-	135
Flash Point COC	°C	220
Pour Point	°C	-33
Total Base Number mg	KOH/g	10,00
Sulphate Ash	%mass	1,33

Volume	Art.no.
1 ltr	310251
4 ltr	310254
5 ltr	310255
20 ltr	3102520
60 ltr	3102560
208 ltr	31025208
bulk	31025

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.