Version : **1.2**
Date : **may 01 2020**

EXCELLO STOU SPECIAL 10W30/15W30

Description

Excello Stou Special is an up-to-date multifunctional lubricating oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to achieve the following properties:
- a powerful dispersion and detergency
- a high activity against wear, corrosion and foam
- a very strong resistance to oxidation
- an excellent extreme pressure properties
- a high and stable viscosity index

Toepassingen

Excello Stou Special is a multifunctional STOU (Super Tractor Oil Universal) oil, developed to be used as one oil for the lubrication of gasoline and diesel engines, transmissions, wet brakes and hydraulic systems in agricultural and earthmoving equipment.

Specifications

API SF/CG-4/GL-4 | ACEA E3, MIL-L-2104D | Ford M2C159-C | John Deere J27 (10W30) | Massey Ferguson CMS M1139/M1144/M1145 MB 227.1 | ZF TE-ML 06B/07B | Allison C4 | Cat TO-2 | Ford M2C134-D | John Deere J20C/D | Massey Ferguson CMS M1135/M1143 | NH 410B (10W30)

Typical Characteristics			10W30	15W30
Density at 15 °C,	kg/l	:	0,884	0.870
Viscosity -20 °C,	mPa.s	:	6000	6200
Viscosity 40 °C,	mm^2/s	:	76,60	66.30
Viscosity 100 °C,	mm^2/s	:	10,50	10.40
Viscosity Index		:	122	144
Flash Point COC,	°C	:	220	220
Pour Point,	°C	:	-35	-40
Total Base Number, mg	KOH/g	:	11,3	11.3
Sulphate Ash,	%	:	1,45	1.55

Volume	Art.no. 10W30	15W30
1 ltr	310361	310351
4 ltr	310364	310354
5 ltr	310365	310355
20 ltr	3103620	3103520
60 ltr	3103660	3103560
208 ltr	31036208	31035208
bulk	31036	31035

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.