Version : **1.1**
Date : **22 Novembre 2024**

HERCULES 220

Description
Hercules is a high grade industrial gear oil, based on mineral oil, under addition of EP (Extreme Pressure) additives.

Applications
This oil can be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.

Specifications
AGMA 9005-F16 (AS) | AIST (US Steel) 224
David Brown S1.53.101 E | DIN 51517-3 CLP
ISO 12925-1 Type CKD

Typical Characteristics

Density at 15 °C,	kg/l	0,893
Viscosity 40 °C,	mm^2/s	220,00
Viscosity 100 °C,	mm^2/s	18,10
Viscosity Index		95
Flash Point ,	°C	245
Pour Point,	°C	-18

Volume	Art.no.
1 ltr	350631
4 ltr	350634
5 ltr	350635
20 ltr	3506320
60 ltr	3506360
208 ltr	35063208
bulk	35063

UTB B.V.
Kamerlingh Onnesweg 28-30
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.