Version : **3**
Date : **23 January 2026**

HERCULES 320

Characteristics
Hercules 320 is formulated with high-quality base oils and additives, resulting in the following properties:

- Contains Extreme Pressure (EP) additives for effective wear protection;
- Long service life thanks to excellent oxidation and thermal stability;
- Excellent corrosion protection;
- Strong resistance to foaming;
- Good functionality at cold temperatures due to a low pour point.

Application
Hercules 320 is a high-quality mineral gear oil for use in industrial gearboxes, gearmotors, and worm gears.

Specifications
Agma 9005-E02 | DIN 51517 CLP | David Brown 51.53.101E | AISE (U.S. Steel) 224

Typical properties

Viscosity Grade		ISO-VG 320
Density at 15°C	kg/L	0,897
Viscosity 40°C	cSt	320
Viscosity 100°C	cSt	24.2
Viscosity Index		94
Flash Point COC	°C	255
Pour Point	°C	-21
FZG test		12

Volume	Art.no.
1 ltr	350641
4 ltr	350644
5 ltr	350645
20 ltr	3506420
60 ltr	3506460
208 ltr	35064208
bulk	35064

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.