PRODUCT DATA SHEET

Versie : 1.1
Datum : 06 januari 2026

OIL FLUSH

Features
UTB Oil Flush cleans and restores the engine. It is used before an oil change to dissolve sludge, deposits and contaminants inside the engine. Suitable for all petrol and diesel engines with catalytic converters and turbochargers. For preventive maintenance and for the removal of sludge and deposits from the lubrication system to support optimal engine performance:

- Supports the restoration of compression
- Improves oil flow
- Suitable for all petrol and diesel engines

Applications
Add one bottle of UTB Oil Flush to the old engine oil before draining. Let the engine idle for 10 to 15 minutes without driving. Then perform a complete oil and filter change.

Volume	Art.no.
24 x 250 ml	7200524250

UTB LUBRICANTS B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.
Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply.