Version : 1.1
Date : 22 Novembre 2024

POWER STEERING FLUID

Description

This is a special hydraulic fluid based on very special advanced base oils to which special additives have been added in order to obtain the following unique properties:

- an exceptional high viscosity index (>300!), obtaining a very positive viscosity development
- a very low pour point
- very strong anti-foaming properties
- a good compatibility with seals

Applications

This special hydraulic fluid is used as a hydraulic agent in very different hydraulic systems, such as power steering systems, leveling sytems, hydraulic pneumatic spring systems, shock absorbing devices, hydrostatic driving gears, ABS/ASR and ASC systems, hydraulically controlled couplings and electro-hydraulic folding roof control systems, etc.

Specifications

ISO 7308, DIN 51524-T3 | Chrysler MS-11655B | DTFR 31B120 | EvoBus 39.060-001
Ford WSS-M2C204-A | MAN M 3289 | MB 345.0 / 345.1 | PSA S71 2710 | ZF TE-ML 02K (ZF004744)
VW G 002 000 (TL 52146) | Bentley JNV862564F | BMW 81229407758 / 82111468041 / 83290429576
Fendt X 902 011 622 | Iveco 18-1807 Classe APU | Opel B 040 0070 |Porsche 000 043 203 33
Saab 3032 380 | Volvo 1161529

Typical Characteristics

Density at 15 °C,	kg/l	0,830
Viscosity 40 °C,	mm^2/s	18,70
Viscosity 100 °C,	mm^2/s	6,00
Viscosity Index		313
Flash Point ,	°C	154
Pour Point,	°C	-57

Volume	Art.no.
1 ltr	320771
4 ltr	320774
5 ltr	320775
20 ltr	3207720
60 ltr	3207760
208 ltr	32077208
bulk	32077

UTB B.V.
Kamerlingh Onnesweg 28-30
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.