Version : **2**
Date : **23 January 2026**

QUALITACK 4152

Characteristics

Qualitack 4152 is a high quality anhydrous calcium thickened lubricating grease based on a mineral oil. The grease contains antioxidants, corrosion inhibitors, EP/AW additives and solid lubricants.

- Very good corrosion protection
- Excellent water resistance
- Pumpable at lower temperatures
- Wide range of use

Application

Qualitack 4152 is suitable for use in a wide range in both industrial and automotive applications. This grease can be used in a wide range of plain and rolling bearings, medium loaded bearings and in wet and corrosive environments. This grease can also be used as a basic stern tube grease. It has excellent adhesion and water resistance

Specifications

ISO 12924: L-XC(F)CIB 2 | DIN 51502: K P2K-30

Typical properties

Thickener		Anhydrous Calcium
Colour		Black
Consistency		NLGI 2
Drop Point	°C	>140
Viscosity 40°C	cSt	110
Viscosity 100°C	cSt	9
4-Ball Weld Load	N	3000
Temperature Continuous	°C	-30 – 120
Temperature Short Period	°C	130

Volume	Art.no.
400 gr	34072
18 kg	3407218

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.