Version : **2**
Date : **23 January 2026**

QUALITACK 6212

Characteristics

QualiTack 6212 is an extremely water- and temperature resistant calcium sulphonate complex grease based on mineral base oils, with excellent adhesion properties, antioxidants and corrosion additives.

- Excellent rust protection
- Excellent water resistance
- Excellent resistance to shock load

Application

QualiTack 6212 is a modern high performance grease for lubrication in industry, shipping, offshore and off road. The extreme load capacity and extreme water resistance make the product ideally suited for heavy loads with applications in corrosive, warm and humid environments.

Specifications

ISO 12924: L-XC(F)CIB 2 | DIN 51502: KP2N-30

Typical properties

Thickener		Calcium Sulphonate Complex
Colour		Brown
Consistency		NLGI 2
Drop Point	°C	>280
Viscosity 40°C	cSt	290
Viscosity 100°C	cSt	18
4-Ball Weld Load	N	6500
Water protection at 90°C		1
Water washing at 79°C		<10%
Temperature Continuous	°C	-30 – 140
Temperature Short Period	°C	180

Volume	Art.no.
400 gr	34091
18 kg	3409118

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.