Version : 1.2
Date : may 04 2020

SYNGEAR 75W90

Description

Syngear 75W90 is a semi-synthetic lubricating oil for mechanical transmissions, formulated with high quality solvent refined and synthetic base oils and special EP-additives to obtain the following properties:
- an excellent resistance against oxidation
- a very high activity against wear, corrosion and foam
- a low pour point
- very good EP-properties
- good clutch-switch performance at low temperatures
- fuel economy

Application

Syngear 75W90 is an universal semi synthetic gear oil for use in manual transmissions and hypoid differentials in passenger cars and delivery vans. This products is useful in gearboxes where mineral EP gear oils give switch problems.

Specifications

API GL-3/GL-4/GL-5/MT-1 | MIL-L-2105D/MIL-PRF-2105E | SAE J2360 | MB 235.8
ZF TE-ML 02B/07A

Typical Characteristics

Density at 15 °C,	kg/l	:	0,879
Viscosity 40 °C,	mm²/s	:	83,00
Viscosity 100 °C,	mm²/s	:	14,80
Viscosity Index		:	188
Flash Point COC,	°C	:	180
Pour Point,	°C	:	-45

Volume	Art.no.
1 ltr	321011
4 ltr	321014
5 ltr	321015
20 ltr	3210120
60 ltr	3210160
208 ltr	32101208
bulk	32101

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.