Version : **1.1**
Date : **22 Novembre 2024**

SYNGEAR ATF 7G

Description
Syngear ATF 7G is a very high graded automatic transmission fluid formulated with a number of special selected base oils and additives. This fluid may be used for automatic transmissions of different car manufacturers as stated below.

Applications
This fluid may be used for automatic transmissions of different car manufacturers as stated below.

Specifications
Allison C4 / TES-389 / TES-295 | BMW 7045E / 8072B / LA2634 / LT71141 | Chrysler ATF+/+2/+3/+4
DTFR 13C110 / 13C140 / 13C150 / 13C170 / 13C180 | Ford Mercon V / Mercon / WSS-M2C922-A1
GM Dexron II/IID/IIE/IIIG/IIIH / TASA | Honda ATF-Z1 (except in CVT) | Hyundai/Kia SP-II/SP-III/RED-1K,
Isuzu ATF II/III | Jaguar JLM 20238/20292/21044 | JASO M315 Type 1A | Mazda M-III/Type T-IV / JWS 3309
MB 236.5 / 236.6 / 236.7 / 236.8 / 236.9 / 236.10 / 236.11 / 236.91 / 236.93
Mitsubishi SP-II/SP-III/J2 | Nissan Matic D/J/K | Subaru ATF HP, Suzuki ATF 3314/3317
Toyota DII/T/T-III/T-IV, Volvo 97341 / 1161540 | VW G 052 025 / 052 055 / G 052 162 / 052 990 / 055 025
ZF TE-ML 11A / 11B

Typical Characteristics

Density at 15 °C,	kg/l	0,862
Viscosity 40 °C,	mm^2/s	33,10
Viscosity 100 °C,	mm^2/s	7,10
Viscosity Index		185
Flash Point ,	°C	200
Pour Point,	°C	-54

Volume	Art.no.
1 ltr	310521
4 ltr	310524
5 ltr	310525
20 ltr	3105220
60 ltr	3105260
208 ltr	31052208
bulk	31052

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.