Version : 1.2
Date : May 04, 2020

SYNGEAR ATF 8HP

Description

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.
- Anti-wear protection : significantly extended transmission life;
- Frictional properties : very smooth gear shifting, no vibration;
- Extended oil life : excellent thermal and oxidation stability.

This superior quality synthetic oil has been designed to provide exceptional protection and extends oil and automatic transmission life. It has excellent cold start properties, very good shear stability, and contributes to fuel saving.

Application

Exclusively intended for the ZF 6,8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

Specifications

BMW 83222152426 | CHRYSLER 68157995AA | FIAT 9.55550-AV5 | JAGUAR 02JDE26444
LAND ROVER LR023288 | VW G 060 162

Typical Characteristics

Density at 15	°C kg/l	0,845
Kin.Viscosity 40	°C, mm²/s	28,1
Kin.Viscosity 100	°C, mm²/s	5,94
Viscosity Index		164
Flash Point COC,	°C	210
Pour Point,	°C	-48
Colour		GREEN
Brookfield viscosity at 40	°C, mPa.s	9500

Volume	Art.no.
1 ltr	321711
4 ltr	321714
5 ltr	321715
20 ltr	3217120
60 ltr	3217160
208 ltr	32171208
bulk	32171

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.