Version : **2**
Date : **23 January 2026**

SYNGEAR ATF CVT

Characteristics
Syngear ATF CVT is a state of the art fluid, that has been very carefully designed to be used in most CVT gearboxes. ATF CVT is suitable for continuously variable transmissions, using steel push-belts or chains. It offers outstanding antiwear protection and stable friction characteristics.

Application
OEMs usually recommend specific CVT fluids for their transmissions. By carefully balancing base oils and advanced additives, it has become possible to formulate this fluid that meets the requirements of both European and Japanese CVT manufacturers.

Specifications
MB 236.17

Typical properties

Density at 15°C	kg/L	0,852
Viscosity 40°C	cSt	34.2
Viscosity 100°C	cSt	7.35
Viscosity Index		189
Pour Point	°C	-45

Volume	Art.no.
1 ltr	310721
4 ltr	310724
5 ltr	310725
20 ltr	3107220
60 ltr	3107260
208 ltr	31072208
bulk	31072

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.