Version : **1.2**
Date : **may 04, 2020**

SYNLUB ATF VI

Description

Synlub ATF VI is a full synthetic lubricant based on carefully selected very high quality base oils, which meets the requirements of the General Motors Dexron VI specification. Its special composition allows it to be used in all applications, where the older Dexron II and Dexron III fluids are recommended.

- Frictional properties : very smooth gear shifting, no vibration.
- Anti-wear protection : significantly extended transmission life.
- Extended oil life : excellent thermal and oxidation stability.

Application

Synlub ATF VI is a fluid that may be used in automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF is required. It exceeds ATF Dexron III and II. Compared with other Dextron types, this liquid has longer lifetime due to its special composition. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended.

Specifications

Dexron VI | GM DEXRON VI/IID/IIE/IIIG/IIIH/TASA | MB 236.41 | VOITH H55.6335xx | Mercon LV MB 236.1/236.2/236.3/236.5/236.7/236.8/236.9 | VAG G-055-025/G-052-055/G-052-162/G-052-990/ G-053-025/G-055-025/G-055-162/G-055-540/G-060-162 | Aisin Warner JWS 3309(T-IV)/3324(WS)/ AW-1 Allison C3/C4 | BMW 7045E/8072B/LA2634 | Mini Cooper T-IV | Chrysler Dodge Mopar AS68RC/69RC (Type IV) | Chrysler ATF+/+2/+3/+4 | Fiat Type IV | Ford Mercon/WSS-M2C138-CJ/166-H/922-A1/924-A Honda Acura DW-1/ATF-Z1(except in CVT) | Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/ SP-IV RR Hyundai/Kia JWS 3314/9683 | Isuzu Besco ATF II/III | Nissan Matic C/D/J/K/S | Jaguar ATF 3403 M115/JLM 20238/20292 | JASO M315-2013 1A/1A-LV/2A | Mazda ATF DII/M-III/M-V/FZ/F-1/S-1/ N-1/3317 Mitsubishi SK/SP-II/SP-III/SP-IV/AW/J2/J3/ATF PA | Opel, Porsche ATF 3403-M115/Type IV | Subaru ATF ATF/AW-1/ATF 5AT/ATF HP | Suzuki ATF 3309/3314/2326/2384K | Toyota D-II/D-III/T-III/ T-IV/WS Volvo 1161540/97340/97335 | ZF 5HP 18FL/19FL/24A/30/4 HP 20, ZF TE-ML 11A/11B

Typical Characteristics

Density at 15 °C	kg/l	0,847
Kin.Viscosity 40 °C,	mm²/s	30
Kin.Viscosity 100 °C,	mm²/s	6.0
Viscosity Index		151
Pour Point,	°C	-45
Colour		RED

Volume	Art.no.
1 ltr	320691
4 ltr	320694
5 ltr	320695
20 ltr	3206920
60 ltr	3306960
208 ltr	32069208
bulk	32069

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.