Version : 1.1
Date : Novembre 22 2024

# SYNGEAR DSG FLUID

## Description
Syngear DSG Fluid is a dual clutch transmission fluid which is developed to fulfill the highest demands of modern high tech dual clutch transmissions and is particularly suitable for transmissions where the dual clutch, synchronizer, gear set and hydraulic control system operate with the same fluid.

## Application
This fluid may is developed to fulfill the highest demands of modern high tech dual clutch transmissions and is particularly suitable for transmissions were dual clutch, synchronizer, gear set and hydraulic control system operate with the same fluid (including hybrid applications).
Suitable for use in DCT transmissions (mainly 6, 7 and 8 speed), like: VW (Audi, Seat, Skoda), BMW Drivelogic, Chrysler Powershift, Geely, Great Wall, Getrag, Ford/Nissan Powershift, Mitsubishi TC-SST, Peugeot/Citroën DCS, Volvo Powershift, Porsche PDK and ZF, in accordance with the specified specifications.

## Specifications
BMW DCTF-1 / 1+/ 2 | BMW MTF LT-5 | Borg Warner | CHRYSLER 68044345EA & GA | DFTR 13C130 | FERRARI TF DCT-F3 | FIAT 9.55550-MZ6 | FORD WSS-M2C936-A / 218-A1 / 200-D2 | Hyundai/Kia | MB 236.21 / 236.22 / 236.24 / 236.25 / 239.21 | MITSUBISHI DIAMOND QUEEN SSTF-1 | NISSAN R35 SPECIAL | PORSCHE 000.043.20 \ 000.043.207.29 \ 000.043.207.30 | PSA 9734 S2 RENAULT BOT450 EDC 6-Speed / DC4 / DW5 / DW6 | VOLVO BOT341 #1161838 / 1161839 / D1 / D2 | VW G 052 182 / G 052 529 / G 052 536 / G 055 529 / G 055 536 | VW TL 52182

## Typical Characteristics

| | | |
|---|---|---|
| Density at 15 °C, kg/l | : | 0,850 |
| Viscosity 40 °C, $mm^2/s$ | : | 34,00 |
| Viscosity 100 °C, $mm^2/s$ | : | 7,17 |
| Viscosity Index | : | 183 |
| Flash Point COC, °C | : | 201 |
| Pour Point, °C | : | -48 |

| Volume | Art.no. |
|---|---|
| 1 ltr | 320601 |
| 4 ltr | 320604 |
| 5 ltr | 320605 |
| 20 ltr | 3206020 |
| 60 ltr | 3206060 |
| 208 ltr | 32060208 |
| bulk | 32060 |

**UTB B.V.**
Kamerling Onnesweg 28-30
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.