# PRODUCT DATA SHEET

**Versie** : **1.2**
**Datum** : **04 may 2020**

# SYNGEAR LD 75W140

## Description

Syngear LD 75W140 is a universal full-synthetic gear oil based on high quality synthetic base oils and special EP-additives to obtain the following properties:
- an excellent activity against high temperature load
- a very strong activity against wear, corrosion and foam
- a low pour point
- very special extreme pressure properties
- widely usable

## Application

Syngear LD 75W140 is an universal gear oil, developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called “Total Drive Line” oil is as universal product widely usable.

## Specifications

API GL4/GL5/MT-1 | ARVIN MERITOR 0-76-N | DAF | IVECO | MACK GO-J
MAN M 342 M3 | MAN 341 Type E-2/Z-2 | MB 235.8 | MIL-PRF-2105 E
SAE J2360 | SCANIA STO:01 | ZF-TE ML 02B/05B/07A/12B/16F/17B/19C/21B | FORD WSS-M2C192-A | FORD WSS-M2C192A+/M2C118-A | FORD WSS-M2C187-A

## Typical Characteristics

| | | | |
|---|---|---|---|
| Density at 15°C, | kg/l | : | 0,876 |
| Viscosity 40 °C, | mm²/s | : | 188,00 |
| Viscosity 100 °C, | mm²/s | : | 25.80 |
| Viscosity Index | | : | 171 |
| Flash Point COC, | °C | : | 252 |
| Pour Point, | °C | : | -48 |

| Volume | Art.no. |
|---|---|
| 1 ltr | 321051 |
| 4 ltr | 321054 |
| 5 ltr | 321055 |
| 20 ltr | 3210520 |
| 60 ltr | 3210560 |
| 208 ltr | 32105208 |
| bulk | 32105 |

**UTB B.V.**
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.