Version : **1.2**
Date : **may 04 2020**

SYNGEAR LD 75W90

Description

Syngear LD 75W90 is an universal full-synthetic gear oil based on high quality synthetic base oils and special EP-additives to obtain the following properties:
- an excellent activity against high temperature load
- a very strong activity against wear, corrosion and foam
- a low pour point
- very special extreme pressure properties
- widely usable

Application

Syngear LD 75W90 is an universal gear oil, developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called “Total Drive Line” oil is as universal product widely usable.

Specifications

API GL-3/GL-4/GL-5/MT-1 | MIL-L-2105D/MIL-PRF-2105E, SAE J2360 | MB 235.8
MAN 341 Typ Z2, 3342 Typ M3 | ZF TE-ML 02B/05A/07A/12L/12N/16B/16F/17B/19C/21A
Scania STO 1:0 | DAF, Iveco, Eaton Europe | Volvo 97312 | Mack GO-J | Ford M2C200-B

Typical Characteristics

Density at 15	°C, kg/l	:	0,865
Viscosity 40 °C,	mm²/s	:	101,00
Viscosity 100 °C,	mm²/s	:	15
Viscosity Index		:	157
Flash Point COC,	°C	:	195
Pour Point,	°C	:	-51
Total Base Number, mg	KOH/g	:	2,1

Volume	Art.no.
1 ltr	321001
4 ltr	321004
5 ltr	321005
20 ltr	3210020
60 ltr	3210060
208 ltr	32100208
bulk	32100

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.