Version : **1.1**
Date : **18 august 2026**

SYNGEAR RACING 75W90

Characteristics
Syngear Racing 75W90 is an advanced, sustainable, ester- and PAO-based transmission oil, specially developed for racing vehicles. The oil's excellent low-temperature viscosity ensures rapid protection for all gears.

Application
This is a special, durable transmission oil with extreme-pressure properties, specifically formulated for use under extreme racing conditions.

Specifications
API GL-5 / MT-1 | ARVIN MERITOR 0-76-E | BMW 83 22 2 365 987 / OSP | CHRYSLER MS 9763 DANA SFU | FIAT 9.55550-DA3 / 9.55550-DA4 / 9.55550-DA6 / 9.55550-DA7 / 9.55550-DA8 / 9.55550-MX4 | MACK GO-J | MCLAREN MOB PTX | PORSCHE 000.043.204.19 / 000.043.204.20 / 000.043.204.71 / 000.043.207.76 / 000.043.210.12 / 000.043.304.71 / 000.043.305.55 / 999.917.062.00 / 999.917.067.00 / 999.917.090.00 / 999.917.545.00 / 999.917.546.00 | SCANIA STO 2:0A FS | SCHMIDT | ZF TE-ML 05A / 05B / 07A / 12N / 16F / 17B / 19C / 21A

Typical properties

Density at 15°C	g/cm³	0,881
Kinematic viscosity 40°C	mm²/s	104,0
Kinematic viscosity 100°C	mm²/s	15,4
Viscosityindex	-	156
Pourpoint	°C	-42

Volume	Art.no.
1 ltr	350811
4 ltr	350814
5 ltr	350815
20 ltr	3508120
60 ltr	3508160
208 ltr	35081208
Bulk	35081

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.