PRODUCT DATA SHEET

Version : **1.1**
Date : **18 august 2026**

SYNGEAR LS RACING 75W140

Characteristics
Syngear LS Racing 75W140 is a durable, high-performance, ester- and PAO-based racing gear oil for the gearboxes and transaxles of race vehicles, offering exceptional wear and extreme-pressure (EP) protection, superior high-temperature resistance, and an extended oil service life.

Application
This durable lubricant can be used in gearboxes, transaxles, and differentials—with or without limited-slip—in racing vehicles.

Specifications
API GL-5 / GL-6 / MT-1 | MIL L-2105 B | 2105 C | 2105 D | 2105 E | SAE J 2360 | ARVIN MERITOR 0-76-N | ASTON MARTIN 6G33-7106-AA/S | BMW 83 22 1 470 080 / 83 22 2 282 583 / 83 22 9 407 803 / 83 22 9 407 870 / MSP/A | CHRYSLER 68218658AA / MS 8985 / FERRARI PAKELO GLOBAL MULTIGEAR DLS | FORD ESW-M2C104-A / ESW-M2C119-A / WSL-M2C192-A + EST-M2C118-A / WSS-M2C187-A | GM 12346140 / 1942386 / 9986226 / 9986290 | MACK GO-J | MB 235.61 | M-SPORT Rally3/Rally4/Rally5/R1/R2/R3 | NISSAN 2189E | SCANIA STO 1:0 SCANIA STO 2:0A | VW G 052 539 ZF TE-ML 05A / 05B / 05C / 05D / 07A / 12D / 12N / 16F / 16G / 19C / 21A / 21C

Typical properties

Density at 15°C	g/cm³	0,898
Kinematic viscosity 40°C	mm²/s	179,0
Kinematic viscosity 100°C	mm²/s	24,3
Viscosityindex	-	167
Pourpoint	°C	-51

Volume	Art.no.
1 ltr	322101
4 ltr	322104
5 ltr	322105
20 ltr	3221020
60 ltr	3221060
208 ltr	32210208
Bulk	32210

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.