**Version** : 1.1
**Date** : 22 Novembre 2024

# SYNLUB 4T 10W40

## Description

A new generation synthetic engine oil for four-stroke motorcycles formulated with synthetic base oils combined with special developed balanced additives to achieve the following properties:

- a high and stable viscosity index
- optimal friction characteristics
- a very strong protection against wear, corrosion and foaming
- a very good detergency and dispersion

## Applications

This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

## Specifications

API SN
JASO MA2
JASO MA

## Typical Characteristics

| | | |
|---|---|---|
| Density at 15 °C, | kg/l | 0,852 |
| Viscosity 40 °C, | $mm^2/s$ | 82,60 |
| Viscosity 100 °C, | $mm^2/s$ | 13,70 |
| Viscosity Index | | 170 |
| Flash Point , | °C | 228 |
| Pour Point, | °C | -33 |
| Total Base Number | mgKOH/g | 7,7 |
| Sulphate Ash | % | 0,85 |

| Volume | Art.no. |
|---|---|
| 1 ltr | 310411 |
| 4 ltr | 310414 |
| 5 ltr | 310415 |
| 20 ltr | 3104120 |
| 60 ltr | 3104160 |
| 208 ltr | 31041208 |
| bulk | 31041 |

**UTB B.V.**
Kamerlingh Onnesweg 28-30
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.