Version : 1.1
Date : 22 Novembre 2024

SYNLUB 4T SCOOTER 5W40

Description
A new generation synthetic engine oil for four-stroke motorcycles formulated with synthetic base oils combined with special developed balanced additives to achieve the following properties:

- a high and stable viscosity index
- optimal friction characteristics
- a very strong protection against wear, corrosion and foaming
- a very good detergency and dispersion

Applications
This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

Specifications
API SN
JASO MA2
JASO MA

Typical Characteristics

Density at 15 °C,	kg/l	0,853
Viscosity 40 °C,	mm^2/s	88,90
Viscosity 100 °C,	mm^2/s	14,30
Viscosity Index		167
Flash Point ,	°C	236
Pour Point,	°C	-36

Volume	Art.no.
1 ltr	310331
4 ltr	310334
5 ltr	310335
20 ltr	3103320
60 ltr	3103360
208 ltr	31033208
bulk	31033

UTB B.V.
Kamerlingh Onnesweg 28-30
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.