Version : 1.2
Date : may 04 2014

SYNLUB 4T RACING 15W50

Description

Synlub 4T Racing 15W50 is a full synthetic lubricant based on carefully selected very high quality base oils for 4-stroke engines, specifically used for competition in very severe circumstances (circuit, cross, enduro, quads). It offers exceptional lubricating power, lowers oil consumption and reduces friction and wear, thereby enhancing the performance and lifetime of your motorcycle.

- outstanding engine cleanliness and durability
- Superior anti-wear and oxidation stability
- Very high temprature stability.

Application

Synlub Racing 4T 15W50 is a high quality full synthetic motor oil based on esters for 4-stroke engines of motorcycles sport (road, competition, circuit, cross, enduro, quad bikes), but can also be used for less heavy duty engines in city traffic and on the road. The oil withstands high temperatures, reduces deposits and prevents the clutch from slipping.

Specifications

API SL | JASO MA/MA2

Typical Characteristics

Density at 15 °C,	kg/l	:	0,854
Viscosity 40 °C,	mm^2/s	:	124
Viscosity 100 °C,	mm^2/s	:	18.00
Viscosity Index		:	162
Flash Point COC,	°C	:	260
Pour Point,	°C	:	-36
Total Base Number, mg	KOH/g	:	6.6

Volume	Art.no.
1 ltr	310321
4 ltr	310324
5 ltr	310335
20 ltr	3103320
60 ltr	3103360
208 ltr	31033208
bulk	31033

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.