PRODUCT DATA SHEET

Version : 1.3
Date : August 6th, 2024

SYNLUB 504.00/507.00 5W30

Description

Synlub 504-507 5W-30 is a fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:
- a lower fuel consumption
- low SAPS content
- suitable for modern catalysts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Applications

Synlub 504-507 5W30 is a fully synthetic engine oil suitable mostly for cars from the brands of Volkswagen,Skoda,Seat,BMW and Mercedes Benz. It can be used for gasoline, LPG and diesel engines with or without particle filter and it also allows extended drain intervals. This oils is also known as “Long life III” for cars from the VAG group.

Meets performance of

ACEA A3,B4,C2, C3 | API SN/CF/SP | BMW Longlife-04 | MB 229.51/ 229.52/ 229,31 | VW 504.00/507.00 | Porsche C30 | VW 503.01

Typical Characteristics

Density at 15 °C	kg/m3	857
Kin. viscosity 40 °C	mm^2/s	69
Kin. viscosity 100 °C	mm^2/s	11,8
Viscosity Index		168
Flash Point, D92	°C	>225
Pour Point	°C	-39

Volume	Art.no.
1 ltr	310521
4 ltr	310524
5 ltr	310525
20 ltr	3105220
60 ltr	3105260
208 ltr	31052208
bulk	31052

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.