Version : **1.3**
Date : **August 5th, 2024**

SYNLUB C4 5W30

Description

Synlub C4 5W30 is a fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils. By applying advanced additives the exceptional performance of this low SAPS motor oil is accentuated.

- a lower fuel consumption
- suitable for modern catalysts
- low combustion ash building (low SAPS)
- a fast cold start
- a safe lubrication film at high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

Synlub C4 5W30 is the latest generation, fully synthetic, high-performance lubricant for Gasoline and diesel engines of passenger cars with or without turbo which are equipped with a DPF and a TWC (Three-Way Catalyst). Specifically formulated to provide superior protection of the after-treatment systems of Renault engines.

Specifications

ACEA C4/C3-16 | Renault RN0720 | MB 226.51/229.31 | Fiat 955535-S4

Typical Characteristics

Density at 15°C	kg/m3	851
Dyn. viscosity -30°C	mPa.s	5800
Kin. viscosity 40°C	mm^2/s	66,2
Kin. viscosity 100°C	mm^2/s	11,6
Viscosity Index		172
Flash Point COC	°C	218
Pour Point	°C	-41
Total Base Number	mgKOH/g	6,7
Sulphate Ash	%	0,49

Volume	Art.no.
1 ltr	310641
4 ltr	310644
5 ltr	310645
20 ltr	3106420
60 ltr	3106460
208 ltr	31064208
bulk	31064

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.