PRODUCT DATA SHEET

Version : **1.1**
Date : **18 august 2026**

SYNLUB COMPRES VRS 46

Characteristics

Synlub Compres VRS 46 is a synthetic compressor oil based on synthetic hydrocarbons, which possess an inherent high resistance to aging. The addition of highly effective additives provides the following properties:
- low tendency toward carbon formation
- good oxidation stability
- good corrosion protection
- effective anti-wear performance
- low volatility

Application

Synlub Compres VRS 46 is a 100% synthetic oil recommended for the lubrication of reciprocating compressors and for the drip-feed lubrication of vane compressors. This compressor oil has a low tendency to form carbon, which minimizes the development of deposits in the discharge area within the compressor's operating temperature range. Its high quality often allows for extended oil-change intervals.

Specifications

ISO 6743-3A DAJ

Typical properties

Density at 15°C	g/cm³	0,833
Kinematic viscosity 40°C	mm²/s	46,4
Kinematic viscosity 100°C	mm²/s	7,98
Viscosityindex	-	144
Flashpoint COC	°C	262
Pourpoint	°C	-57

Volume	Art.no.
1 ltr	350811
4 ltr	350814
5 ltr	350815
20 ltr	3508120
60 ltr	3508160
208 ltr	35081208
Bulk	35081

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply.
Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.