Version : 1.2
Date : october 14, 2024

SYNLUB EHPD PLUS 10W40

Description

Synlub EHPD Plus 10W40 is a top quality diesel engine oil based on the latest additive technology combined with very special base oils. This engine oil has the following properties:
- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against wear, corrosion and foam
- a high and stable viscosity index
- a low sulphated ash number
- prolonged oil drain intervals

Application

Synlub EHPD plus 10W40 is a top quality synthetic motor oil, specially developed for Euro 4,5 and 6 engines with or without low-sulphur diesel and particulate filters. Because of the long list of specifications, this product is widely applicable.

Specifications

ACEA E4/ E6/E7/E9 | API CK-4/CJ-4 | Carterpillar ECF-3/2/1a | Cummins CES 20081 | Detroit Diesel 93K218 | Deutz DQC-IV-10 LA | Scania Low Ash | MTU type 3.1/2.1 | MB 228.51 MAN M3271-1 | MAN M3477 (**approval**) | Mack EO-O-PP (**approval**) | Renault RLD-3 (**approval**) Volvo VDS- 4 / 4.5 (**approval**)

Typical Characteristics

Density at 15 °C,	kg/l	:	0,864
Viscosity 40 °C,	mm²/s	:	95,3
Viscosity 100 °C,	mm²/s	:	14,2
Viscosity Index		:	152
Flash Point COC,	°C	:	210
Pour Point,	°C	:	-39
Total Base Number, mg	KOH/g	:	9,5
Sulphate Ash,	%	:	0,99

Volume	Art.no.
1 ltr	310841
4 ltr	310844
5 ltr	310845
20 ltr	3108420
60 ltr	3108460
208 ltr	31084208
bulk	31084

FUGLESANGS TECH
Smøremidler • Hydraulikk • Belegg • Service

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.