Version : 1.3
Date : August 5th, 2024

SYNLUB EXCEL 10W40

Description

Synlub Excel 10W40 is a modern, all-round motor oil based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:
- a lower fuel consumption
- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a very good detergency and dispersion
- a safe lubrication film at high temperatures
- a very strong protection against wear, corrosion and foaming
- a very low oil consumption

Application

Synlub Excel 10W40 is an all-round, fuel economy motor oil based on semi-synthetic base oils and is recommended for use in gasoline- and diesel engines, with or without turbocharging, in passenger cars and delivery vans. This motor oil is developed for automobiles (< year 2002) that ask a high quality oil composition.

Meets performance of

ACEA A3/B3-10/B4-08 | API SL/CF | MB 229.1 | VW 501.01/505.00

Typical Characteristics

Density 15° C	kg/m3	862
Viscosity, 40 °C	mm2/s	90,1
Viscosity, 100°C	mm2/s	13,8
Viscosity index	-	155
Flash Point, COC	°C	220
Pour Point	°C	-33
TBN mg	KOH/g	8,0
Sulphate Ash	%mass	1,0

Volume	Art.no.
1 ltr	310551
4 ltr	310554
5 ltr	310555
20 ltr	3105520
60 ltr	3105560
208 ltr	31055208
bulk	31055

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.