Version : 1.2
Date : may 04 2020

SYNLUB FS 2-STROKE

Description

Synlub FS 2-Stroke is a full-synthetic low viscosity two stroke engine oil formulated with carefully selected high quality synthetic base oils and special two stroke additives to achieve the following properties:
- a perfect lubrication of all motor parts
- a very active detergency, preventing from deposits in the combustion zone and at the scavenger ports
- preventing spark plugs from fouling, in this way securing an optimal output of the engine
- a very strong activity against wear and corrosion
- a very limited formation of smoke
- self-mixing
- red coloured

Application

Synlub FS 2-stroke is a low viscosity two stroke engine oil which is specially suitable for the lubrication of high speed two stroke engines under heavy duty load. This selfmixing two stroke engine oil is also advised for use in two stroke scooters, on which often radiator coolers are fitted.

Specifications

API TC | JASO FD | ISO-L-EGD | Husqvarna | Piaggio Hexagon

Typical Characteristics

Density at 15 °C,	kg/l	:	0,873
Viscosity 40 °C,	mm^2/s	:	48.00
Viscosity 100 °C,	mm^2/s	:	8.90
Viscosity Index		:	168
Flash Point COC,	°C	:	88
Pour Point,	°C	:	-45
Total Base Number, mg	KOH/g	:	2.9

Volume	Art.no.
1 ltr	310311
4 ltr	310314
5 ltr	310315
20 ltr	3103120
60 ltr	3103160
208 ltr	31031208
bulk	31031

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.