Version : **1.2**
Date : **may 04 2020**

SYNLUB OUTBOARD 4T 25W40

Description

Synlub Outboard 4T 25W40 is a four stroke engine oil for outboard application, formulated with carefully selected high quality base oils and special four stroke additives to achieve the following properties:
- a perfect lubrication of all motor parts
- a very active detergency, resulting in a cleaner motorcompartment
- good cold start properties
- a very strong activity against wear, oxidation and corrosion
- excellent shear stability

Application

Synlub Outboard 4T 25W40 is a semi-synthetic 4-stroke engine oil, specially developed to meet the requirements of the NMMA FC-W specification. Synlub Outboard 4T 25W45 is specifically designated for the lubrication of modern 4-stroke outboard and in-board engines including Mercury Marine and Yamaha. This oil provides increased protection against corrosion, even in salt water.

Specifications

NMMA FC-W | API SJ/SL

Typical Characteristics

Density at 15 °C,	kg/l	:	0,892
Viscosity 40 °C,	mm^2/s	:	151.90
Viscosity 100 °C,	mm^2/s	:	15.50
Viscosity Index		:	104
Flash Point COC,	°C	:	244
Pour Point,	°C	:	-21
Total Base Number, mg	KOH/g	:	7.7

Volume	Art.no.
1 ltr	310651
4 ltr	310654
5 ltr	310655
20 ltr	3106520
60 ltr	3106560
208 ltr	31065208
bulk	31065

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.