Version : 1.1
Date : oktober 30 2018

SYNLUB RACING 10W60

Description

Synlub Racing 10W60 is a fully synthetic engine oil based on carefully selected high quality synthetic base oils, all of which already have a natural, high viscosity index and which advanced and well balanced additives in order to obtain the following properties:
- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application

Synlub Racing 10W60 is a fully synthetic engine oil, designed for cars where the highest performance is required. This oil has proven its quality under the most extreme conditions, particularly in races.

Specifications

ACEA A3/B4 | API SN/CF | VW 501 01 / 505 00

Typical Characteristics

Density at 15°C,	kg/l	0,866
Viscosity 40°C,	mm²/s	171
Viscosity 100°C,	mm²/s	24.50
Viscosity Index		175
Flash Point COC,°C		238
Pour Point,°C		-36
Total Base Number,	mgKOH/g	9,6
SulphateAsh,	%	1,1

Volume	Art.no.
1 ltr	310691
4 ltr	310694
5 ltr	310695
20 ltr	3106920
60 ltr	3106960
208 ltr	31069208
bulk	31069

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.