Version : 1
Date : September 26 2014

SYNLUB RACING 5W50

Description

Synlub Racing 5W50 is a fully synthetic engine oil based on carefully selected high quality synthetic base oils, all of which already have a natural, high viscosity index and which advanced and well balanced additives in order to obtain the following properties:
- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application

Synlub Racing 5W50 is a fully synthetic engine oil, designed for cars for where the highest performance is required. This oil has proven its quality under the most extreme conditions, particularly in races.

Specifications

ACEA A3/B4-08 | API SN/CF | BMW Longlife-01 | MB 229.3 | VW 501.01/505.00

Typical Characteristics

Density at 15	°C, kg/l	0,858
Viscosity -30	°C, mPa.s	6450
Viscosity 40	°C, mm^2/s	123.10
Viscosity 100	°C, mm^2/s	19.00
Viscosity Index		175
Flash Point COC,	°C	236
Pour Point,	°C	-57
Total Base Number,	mgKOH/g	10.5
SulphateAsh,	%	1,33

Volume	Art.no.
1 ltr	310751
4 ltr	310754
5 ltr	310755
20 ltr	3107520
60 ltr	3107560
208 ltr	31075208
bulk	31075

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.