PRODUCT DATA SHEET

Version : **1.1**
Date : **June 1 2026**

SYNLUB SUPREME FE 0W20

Characteristics

Synlub Supreme FE 0W20 is a modern and highly fuel-efficient motor oil (petrol, diesel) for vehicles with modern exhaust gas aftertreatment and long maintenance intervals to meet all automotive manufacturers' specifications. The product has been specially developed for BMWs that must comply with BMW LL 17FE+. This specification cannot be used backwards. The product is formulated with PAO base oils.

Application

Synlub Supreme FE 0W20 is suitable for passenger cars, light commercial vehicles, and electric vehicles with petrol or diesel engines and modern exhaust gas aftertreatment. It is also suitable for hybrid cars and may potentially be suitable for engines with an auxiliary petrol tank (please consult specific OEM regulations for this).

Specifications

API SQ RC | ACEA C5, C6 | ILSAC GF-7A | BMW LL 14FE+/17FE+ | MB-229.71/229.72 | Opel OV0401547 | Volvo VCC RBS0-2AE / Volvo VCC C6SP | Chrysler MS 12145 | Fiat 9.55535-GSX | Ford WSS-M2C947-B1/ Ford WSS-M2C954-A1 / Ford WSS-M2C962-A1 | Jaguar Land Rover JLR STJLR 03.5006 | VW VWC 53057

Typical properties

Density at 15°C	g/cm³	0,825 - 0,865
Kinematic viscosity 100°C	mm²/s	7,7 - 8,8
Total base number	mg KOH/g	7,4 - 9,2
Flashpoint COC	°C	Min. 200
Pour point	°C	Max. -48

Volume	Art.no.
1 ltr	311041
4 ltr	311044
5 ltr	311045
20 ltr	3110420
60 ltr	3110460
208 ltr	31104208
Bulk	31104

UTB B.V.
Kamerlingh Onnesweg 28
3316 GL Dordrecht
The Netherlands

T: +31(0)88 - 0202300
F: +31(0)88 - 0202399

I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.