Version : **1.1**
Date : **Novembre 22 2024**

TRANSMISSION ALCAT 10W

Description

Transmission Alcat 10W is a special oil for hydraulic- and transmission equipment formulated with solvent refined base oils and selected additives to obtain the following properties:
- a low pour point
- a very good stability against oxidation
- excellent anti-wear properties, that gives a longer duration of the final drive
- applicable in systems with “wet” brakes
- excellent corrosion and foaming preventive properties

Application

This oil is special developed for the lubrication of power shift transmissions, differentials, final drives and hydraulic equipment of earth-moving equipment, for which a Caterpillar TO-4 or Allison C4 fluid is required.
This oil cannot be used in engines.

Specifications

API GL-4 | Allison C4 | Cat TO-4 / TO-2 | Komatsu KES 07.868.1 | ZF TE-ML 03C | Eaton (Vickers) M-2950-S / I-286-S

Typical Characteristics

Density at 15 °C, kg/l	:	0,884
Viscosity -25 °C, mPa.s	:	5460
Viscosity 40 °C, mm^2/s	:	37,90
Viscosity 100 °C, mm^2/s	:	6,05
Viscosity Index	:	103
Flash Point COC, °C	:	226
Pour Point, °C	:	-30
Sulphate Ash, %	:	1,32

Volume	Art.no.
1 ltr	321151
4 ltr	321154
5 ltr	321155
20 ltr	3211520
60 ltr	3211560
208 ltr	32115208
bulk	32115

UTB B.V.
Kamerling Onnesweg 28-30
3316 GL Dordrecht
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.