Version : 1.2
Date : may 01 2020

TRANSMISSION OIL UTTO

Description

Transmission oil UTTO is an universal hydraulic and transmission oil formulated with solvent refined base oils and selected additives to obtain the following properties:
- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

Application

Transmission oil UTTO is an Universal Tractor and Transmission Oil, specially developed as a lubricant for hydraulic and transmission systems of the most common agricultural and construction machinery. This product is versatile due to its special additive package.

Specifications

API GL-4 | Allison C4 Case MS1206/MS1207/MS1209 | Cat TO-2 | Ford M2C134-D | John Deere J20C | Massey Ferguson M1135/M1143 | NH 410B | Volvo WB 101 | ZF TE-ML 03E/05F/06K

Typical Characteristics

Density at 15 °C,	kg/l	:	0,883
Viscosity 40 °C,	mm^2/s	:	67,00
Viscosity 100 °C,	mm^2/s	:	10,70
Viscosity Index		:	147
Flash Point COC,	°C	:	225
Pour Point,	°C	:	-35
Total Base Number, mg	KOH/g	:	7,3
Sulphate Ash, %		:	1,19

Volume	Art.no.
1 ltr	321101
4 ltr	321104
5 ltr	321105
20 ltr	3211020
60 ltr	3211060
208 ltr	32110208
bulk	32110

UTB B.V.
Mandenmakerstraat 21-25
2984 AS Ridderkerk
The Netherlands
T: +31(0)88 - 0202300
F: +31(0)88 - 0202399
I: www.utb.nl
E: info@utb.nl

Mentioned product values are indicative typical values. UTB BV can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply. Vermelde productwaarden zijn indicatieve typische waarden. UTB BV kan niet aansprakelijk worden gehouden voor eventuele druk- of zetfouten. Op al onze transacties zijn onze algemene leverings- en verkoopvoorwaarden van toepassing.