Trusted for Generations

H.S.T.N: 34031910
REF: MKT.PDS.110
REV: 3

VICKERLUBE FGS SIL SPRAY



DESCRIPTION

VICKERLUBE FGS SIL SPRAY is a high performance, food grade, multipurpose, silicone lubricant spray. It is registered to H1 for incidental food contact for use in and around food, beverage and pharmaceutical processing and production areas.

APPLICATIONS

VICKERLUBE FGS SIL SPRAY is designed for all applications where a light, wet film, long life lubricant is required in the food and other clean industries such as cosmetics and the pharmaceutical industry. It is an excellent non-stick lubricant with very good high temperature resistance. It has very good water, chemical and oxidation resistance properties.

Applications include: -

- Slideways and chutes
- Chains
- Linkages, pins and other components
- Corrosion protection
- Multipurpose light lubrication

CERTIFICATION

VICKERLUBE FGS SIL SPRAY is NSF H1 Registered for incidental food contact, Halal Certified, Kosher Certified, manufactured to ISO 9001:2015 and meets the requirements of FDA 21 CFR 178.3570

FEATURES AND BENEFITS

• NSF H1 Registered	Safe to use where incidental food contact may occur
• Light adhesive lubricant	Stays in place and reduces reapplication
• Excellent wear protection	Elongates component life
• Oxidation and corrosion inhibited	Increases product life & protects against corrosion
• Excellent water resistance	Elongates component life
• High Temperature resistance	Safe in elevated temperatures

METHOD OF APPLICATION

Shake can thoroughly before use. Apply a thin, even coating onto surface from approximately 15 – 30 cm (6 to 12 inches). Apply VICKERLUBE FGS SIL SPRAY sparingly. Store in a cool, dry place, out of direct sunlight. Storage temperature should be below 50°C.

BENJN R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Food Grade
Manufacturing Facility
Unit 2 Knowsthorpe Approach,
Cross Green, Leeds,
LS9 0DW, United Kingdom

Tel: +44 (0)113 386 7654
Email: inbox@vickers-oil.com
Web: www.vickers-oil.com

Follow us on

Certified to the ISO 9001 Quality Standard and the ISO 14001 Environmental Management Standard

FM 01851 EMS 40717

Trusted for Generations

H.S.T.N: 34031910
REF: MKT.PDS.110
REV: 3

VICKERLUBE FGS SIL SPRAY



TYPICAL CHARACTERISTICS AND PROPERTIES

VICKERLUBE FGS SIL SPRAY	RESULT
Appearance	Clear liquid
Base Oil	Silicone oil
Propellant	Propane / Butane
Service Temperature Range (°C)	-50°C to 200°C
Shelf Life	5 years in original sealed containers whilst stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

BENJN R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Food Grade
Manufacturing Facility
Unit 2 Knowsthorpe Approach,
Cross Green, Leeds,
LS9 0DW, United Kingdom

Tel: +44 (0)113 386 7654
Email: inbox@vickers-oil.com
Web: www.vickers-oil.com

Follow us on

Certified to the ISO 9001 Quality Standard and the ISO 14001 Environmental Management Standard

FM 01851 EMS 40717